

Thanks for purchasing this High Fidelity USB DAC Headphone Amplifier from me.
I appreciate that very much!

To use the **HOTAUDIO MARK VII** follow these directions.

1. Plug HEADPHONES OR POWER AMPLIFIER OR BOTH into headphone amplifier.
2. **NEVER USE HEADPHONES WITH LESS THEN 16-OHMS COMBINED IMPEDANCE!**
3. Plug USB cable into the USB port of your computer and turn computer on. (If it is not already on.)
4. Computer should self-install drivers. This could take a few minutes.
5. You should hear a BEEP in your headphones when drivers are installed.
Play your tunes and listen to your music ☺
6. **NOTE: Sometimes when plugging in the USB DAC it will change MAIN Volume setting to ½ volume.**
7. Simply go to the MAIN volume setting (double click small speaker icon on PC's) and put it all the way up.
8. RED RCA IS LEFT CHANNEL – WHITE RCA IS RIGHT CHANNEL

NOTE: THERE ARE NO USER SERVICABLE PARTS INSIDE THIS HEADPHONE AMPLIFIER.

ALSO NOTE: This unit requires a ‘burn-in’ period to achieve its full sonic potential.

Usually after a few hours you will notice a big difference in the sound quality.

DO NOT OPEN THIS UNIT! OPENING IT WILL DESTROY IT!!!!



©1998 - 2009 WWW.HOTAUDIO.COM

Also Check out my forum at <http://www.hotaudio.com/forum/>