

# **HOTAUDIO.COM – HOTUSB1      DEC-02-2009**

## **High Fidelity USB DAC Headphone Amplifier**

To use this headphone amplifier follow these directions.

1. Plug Headphones into headphone amplifier.
2. **NEVER USE HEADPHONES WITH LESS THEN 16-OHMS IMPEDANCE!**
3. Plug USB cable into the USB port of your computer and turn computer on. (If it is not already on.)
4. Computer should self-install drivers. This could take a few minutes.
5. You should hear a BEEP in your headphones when drivers are installed.
6. Play your tunes and listen to your music ☺
7. **NOTE: Sometimes when plugging in the USB DAC it will change MAIN Volume setting to ½ volume.**
8. Simply go to the MAIN volume setting (double click small speaker icon on PC's) and put it all the way up.
9. **NOTE: In iTunes there is a setting you MUST select to enable the USB DAC ( preferences in iTunes ).**

**NOTE: THERE ARE NO USER SERVICABLE PARTS INSIDE THIS HEADPHONE AMPLIFIER.**

**ALSO NOTE: This unit requires a 'burn-in' period to achieve its full sonic potential. Usually after a few hours you will notice a big difference in the sound quality.**

**DO NOT ATTEMP TO OPEN THIS USB DAC AS THERE IS COPY PROTECTION CIRCUITS INSIDE THIS UNIT.**

**OPENING UNIT WILL DESTROY IT!!!**

**DO NOT REMOVE BOTTOM COVER!**

**Check out our new online store at:**

**<http://www.hotaudio.com/zen-cart/>**

**And the new HOTAUDIO.COM forums:**

**<http://www.hotaudio.com/forum/>**

**© 1998 - 2009 WWW.HOTAUDIO.COM**